



N°	Designation	Material
1	Body	GS-C25
2	Seat	13Cr
3	Disk	GS-C25 + 13Cr
4	Disk pin	13Cr
5	Stem	13Cr
6	Bowl board	13Cr
7	Belows	SS304
8	Bonnet bolt	A193 B7
9	Bonnet nut	A194 Gr 2H
10	Stem packing	Graphite
11	Bonnet	GS-C25
12	Stop plank	13Cr
13	Stop plank	Steel
14	Stem nut	ZcuAl10Fe3
15	Handwheel	Steel
16	Handwheel nut	Steel

- Design acc. to EN 13709
- F to F dimensions EN 558-1 S1 (DIN 3202 F1)
- Flange ends dimensions acc. EN 1092-1
- Stainless steel bellows double walled
- Pressure test acc. to EN 12266
- Tongue/groove flanges on request
- PED 97/23/CE - hazard category III

DN	d	D	D1	D2	L	H	n	d	b	Dk
15	15	95	65	45	130	191	4	14	16	130
20	20	105	75	58	150	191	4	14	16	130
25	25	115	85	68	160	200	4	14	16	130
32	32	140	100	78	180	200	4	18	18	130
40	40	150	110	88	200	218	4	18	18	150
50	50	165	125	102	230	220	4	18	20	150
65	65	185	145	122	290	238	8	18	22	180
80	80	200	160	138	310	257	8	18	24	180
100	100	220	190	162	350	340	8	22	24	200
125	125	250	220	188	400	360	8	26	28	220
150	150	285	250	218	480	390	8	26	28	400
200/25	200	360	310	278	600	530	12	26	30	400
200/40	200	375	320	285	600	530	12	30	34	400

Test conditions	
Cold water	60 bar
Air	6 bar

Service conditions	
	40 bar - 120°C
	Acc. to legislation

*Above data shall be considered indicative and not binding.